

Design:

➤ Options:

max. 600 m special PE pipe 110 x 12,3 mm - 10 mm - 8,2 mm
max. 550 m special PE pipe 120 x 12,3 mm - 11,0 mm - 9,0 mm
max. 500 m special PE pipe 125 x 11,4 mm - 9,3 mm

- Special gearbox (4 gears) with adjustable band brake
- Full casing
- P.T.O. shaft fast rewind
- Hydraulic support legs at the back
- Return stop at the pipe drum
- Mechanical safety shut-down against winding faults
- Low pressure - and total shut-down
- Fully galvanized water inlet from both sides (depending on shut-down option)
- Chassis with tandem pendulum axle
- Adjustable for 3 tracks: 1.800, 2.000 and 2.250 mm
- Electronic speed control with pinion sensor,
 - Pre- and after irrigation 0-99 min
 - Different speeds 5-200 m/h (depending on water conditions) for each irrigation cycle possible
 - Display of irrigation time
 - Simple programming
- Sprinkler skid, with automatic lifting
- Large-area sprinkler TWIN 160 ULTRA

Optional equipment:

- Large-area sprinkler at choice
- Compressed air brake system incl. operating licence acc. to Road Traffic Act (StVO)
- Pendulum locking of the tandem axle
- Lockable turntable
- Hydraulic drive for turntable
- Hydraulic support leg at the front
- Pipe guidance device (mechanical or fully hydraulic)
- Supply hose DN 100, 8 m, 108 female/male,
Discharge hose DN 100, 5 m, 108 female
- Water meter DN 100 non-calibrated or calibrated (on request)
- Lighting installation
- Solar panel for battery recharging
- Supply hose reel for 10 m flat hose DN 100
- GSM control
- Additional sprinkler for close range (electronically controlled)
- Wide tires

Applications:

- Agricultural areas, approx. 60 ha
- Vegetable cultivation
- Special crops
- Environmental protection (dust binding etc.)

**Data and dimensions:**

Length ¹⁾ mm	Width mm	Height mm	Track mm	Weight without PE pipe
6.250	2.890	4.000	1.800/2.000/2.250	3.380 kg
Ground clearance mm			Tires	
465			260/70-15.3 AW 14PR	

PE pipe (mm)	Weight (kg/m)	Weight of PE pipe (kg)
∅ 110 x 12,3 - 10,0 - 8,2	2,95 without water	at 600 m length = 1.767
	9,55 with water	at 600 m length = 5.728
∅ 120 x 12,3 - 11,0 - 9,0	3,40 without water	at 550 m length = 1.868
	11,36 with water	at 550 m length = 6.248
∅ 125x11,4 - 9,3	3,57 without water	at 500 m length = 1.785
	12,32 with water	at 500 m length = 6.162

Sprinkler type	Unit	TWIN 160 ULTRA					
Nozzle diameter	mm	20	22	24	26	28	30
Nozzle pressure	bar	3,0					
Water consumption	m³/h	26,9	32,4	38,5	45,6	52,6	60,4
Sprinkler throw range (WW)	m	39,9	41,0	42,0	42,3	42,5	42,8
Irrigated area ²⁾	m	67,8	69,7	71,4	71,9	72,3	72,8
Nozzle pressure	bar	4,0					
Water consumption	m³/h	31,0	37,4	44,5	52,6	60,7	69,7
Sprinkler throw range (WW)	m	43,2	45,3	47,3	49,5	49,5	53,1
Irrigated area ²⁾	m	73,4	77,0	80,4	84,2	84,2	90,3
Nozzle pressure	bar	5,0					
Water consumption	m³/h	34,7	41,8	49,7	58,8	67,9	78,0
Sprinkler throw range (WW)	m	46,2	48,5	50,8	53,4	55,9	58,3
Irrigated area ²⁾	m	78,5	82,5	86,4	90,8	95,0	99,1

1) Length without sprinkler skid

2) Usable irrigated area = 2 x WW -15% for overlapping and loss due to wind

Subject to technical modifications and changes in scope of supply!

HÜDIG - your partner to solve water problems.

HÜDIG®

GmbH & Co. KG

Absenk- und Beregnungsanlagen

 Heinrich-Hüdig-Straße 2 · 29227 Celle
 Telefon (0 51 41) 88 45-0 · Fax (0 51 41) 8 69 18
 e-mail: info@huedig.de