

HÜDIG Irrigation Machine

HÜDIG®

Type Iromat II RED

www.huedig.de

Design:

max. 400 m special PE pipe 110 x 8,2 mm

- Special gearbox (4 gears) with adjustable band brake
- Full casing
- P.T.O. shaft fast rewind
- Hydraulic support legs at the back
- Return stop at the pipe drum
- Mechanical safety shut-down against winding faults
- Low pressure - and total shut-down
- Fully galvanized water inlet
- Chassis with single axle
- Tracks adjustable: 1.500 mm – 2.000 mm
- Electronic speed control with pinion sensor,
 - Pre- and after irrigation 0-99 min
 - Different speeds 5-200 m/h (depending on water conditions) for each irrigation cycle possible
 - Display of irrigation time
 - Simple programming
- Sprinkler skid, with automatic lifting
- Large-area sprinkler TWIN 140 ULTRA

Optional equipment:

- Large-area sprinkler at choice
- Compressed air brake system incl. operating licence acc. to Road Traffic Act (StVO)
- Lockable turntable
- Hydraulic drive for turntable
- Hydraulic support leg at the front
- Pipe guidance device (mechanical or fully hydraulic)
- Supply hose DN 90, 8 m, 89 female/male, Discharge hose DN 90, 5 m, 90 female
- Water meter DN 80 non-calibrated or calibrated (on request)
- Lighting installation
- Solar panel for battery recharging
- Supply hose reel for 12 m flat hose DN 90
- GSM control
- Additional sprinkler for close range (electronically controlled)
- Wide tires

Applications:

- Agricultural areas, approx. 40 ha
- Vegetable cultivation
- Special crops
- Environmental protection (dust binding etc.)



Data and dimensions:

Length ¹⁾ mm	Width mm	Height mm	Track mm	Weight without PE pipe
5.800	2.750	3.500	1.500 - 2.000	2.630 kg
Ground clearance mm			Tires	
600			11.5/80-15.3 AW 14PR	

PE pipe (mm)	Weight (kg/m)	Weight of PE pipe (kg)
∅ 110x8,2	2,66 without water	at 400 m length = 1.065
	9,54 with water	at 400 m length = 3.817

Sprinkler type	Unit	TWIN 140 ULTRA					
		16	18	20	22	24	26
Nozzle diameter	mm	16	18	20	22	24	26
Nozzle pressure	bar	3,0					
Water consumption	m³/h	16,9	21,4	26,5	31,9	38,0	44,9
Sprinkler throw range (WW)	m	35,5	37,6	39,7	40,8	41,8	42,1
Irrigated area ²⁾	m	60,4	63,9	67,5	69,4	71,1	71,6
Nozzle pressure	bar	4,0					
Water consumption	m³/h	19,5	24,7	30,7	36,9	43,9	51,8
Sprinkler throw range (WW)	m	37,5	37,7	41,8	43,8	45,7	47,8
Irrigated area ²⁾	m	63,8	67,5	71,0	74,5	77,7	81,2
Nozzle pressure	bar	5,0					
Water consumption	m³/h	21,8	27,6	34,3	41,2	49,1	58,0
Sprinkler throw range (WW)	m	40,0	42,6	45,1	47,3	49,5	52,1
Irrigated area ²⁾	m	68,0	72,4	76,7	80,4	84,2	88,6

1) Length without sprinkler skid

2) Usable irrigated area = 2 x WW –15% for overlapping and loss due to wind

Subject to technical modifications and changes in scope of supply!

HÜDIG - your partner to solve water problems.

HÜDIG®

GmbH & Co. KG

Absenk- und Beregnungsanlagen

Heinrich-Hüdig-Straße 2 · 29227 Celle
 Telefon (0 51 41) 88 45-0 · Fax (0 51 41) 8 69 18
 e-mail: Info@huedig.de