

Issue 08/17	Technical Data	HÜDIG® www.huedig.de
HÜDIG Power Set		
STEP 400 ECON		



General technical data, approx.:

Length:	4000 mm
Width:	1250 mm
Height:	2200 mm
Weight (dry):	3900 kg
Tank volume:	230 l
Tank volume sufficient for:	3 h / 75% load
Sound pressure level (7m):	70 dB (A)
calculated sound pressure level:	LPA _{7m} =69 dB(A) LPA _{10m} =67dB(A)

Generator:

Brand:	Mecc Alte
Type:	ECO40-1S
Apparent power:	400 kVA
3 ~ cos φ:	0,8
Voltage 3 ~:	400 V
Voltage 1~:	230 V
Frequency:	50 Hz
Current 3 ~:	577 A
Overload:	10% of the rated output every 6 h for 1 h
Protection class:	IP 21

Motor:

Brand:	Iveco
Type:	CURSOR 13TE3A
Emission class:	STAGE II
Number of cylinders:	6
Output (PRP):	366,2 kW
Speed:	1500 min ⁻¹
Fuel:	Diesel
Fuel consumption	
at 100% load:	85,8 l/h
at 50% load:	42,8 l/h

Electrical connection via sockets:

1 x terminal strip (generator main switch)

Features

Emergency stop button
 Operation via central control panel
 Voltmeter
 Amperemeter
 Frequency display
 Operating hours counter
 Fuel shortage signal (reserve)
 Electronic voltage regulator
 Motor automatic switch-off:
 - excessive temperature
 - oil pressure lack
 - fuel shortage
 Lockable doors
 Lifting holes for forklift trucks
 Central crane lugs
 Integrated emission sound absorber
 Closed oil drip pan

Optional Accessories

Tank level display
 80 km/h chassis
 - Truck or
 - Car traction device mounted
 - Including TÜV testing
 Earth rod

Subject to technical modifications

HÜDIG - your partner to solve water problems.

HÜDIG®
 GmbH & Co. KG

Absenk- und Berechnungsanlagen

Heinrich-Hüdig-Straße 2 · 29227 Celle
 Telefon (0 51 41) 88 45-0 · Fax (0 51 41) 8 69 18
 e-mail: Info@huedig.de