



Dimensions	Parameter	Unit	Value
	Length ¹⁾	mm	4.420
	Width ²⁾	mm	2.250
	Height	mm	2.790
	Track	mm	1.500 – 1.800
	Weight, unloaded ^{1), 3)}	kg	1.450
	Ground clearance	mm	530
	Tires		10,0/80-12 AW, 10PR

¹⁾ Without sprinkler skid, ²⁾ Depending on the equipment of the machine, ³⁾ Without PE-pipe

Weights	Parameter	Unit	Value		
	PE-pipe Ø 63 mm x 380 m	kg	without water	326	
		kg	with water	1.183	
	PE-pipe Ø 75 mm x 325 m	kg	without water	389	
		kg	with water	1.434	
	PE-pipe Ø 82 mm x 300 m	kg	without water	428	
kg		with water	1.583		

Available with the following PE pipe sizes:

- max. 380 m special PE-pipe Ø 63 x 4,7 mm
- max. 325 m special PE-pipe Ø 75 x 5,5 mm
- max. 300 m special PE-pipe Ø 82 x 6,0 mm

Applications

in agriculture – forestry – industry

- Agriculture areas, up to approx. 25 ha
- Vegetable cultivation
- Fruit growing
- Special crops
- Tree nurseries
- Sports fields
- Composting plants

Sprinkler	Parameter	Unit	TWIN 101 ULTRA				
	Nozzle diameter	mm	14	16	18	20	22
	Nozzle pressure	bar	3,0				
	Water consumption	m ³ /h	13,0	16,9	21,4	26,5	31,9
	Throw range (WW)	m	31,6	33,7	35,9	38,2	39,1
	Effective irrigation width ⁴⁾	m	53,7	57,3	61,0	65,0	66,5
	Nozzle pressure	bar	4,0				
	Water consumption	m ³ /h	15,1	19,5	24,7	30,7	36,9
	Throw range (WW)	m	35,1	37,3	39,9	42,5	44,2
	Effective irrigation width ⁴⁾	m	59,7	63,4	67,8	72,3	75,1
	Nozzle pressure	bar	5,0				
	Water consumption	m ³ /h	16,8	21,8	27,6	34,3	41,2
	Throw range (WW)	m	37,3	39,8	42,5	45,2	47,3
	Effective irrigation width ⁴⁾	m	63,4	67,7	72,3	76,8	80,4

⁴⁾ Effective irrigation width = 2xWW-15% for overlapping and loss due to wind

Standard equipment

- Portal axle chassis, single-axle with high ground clearance
- Adjustable track: 1.500 – 1.800 mm
- Agriculture-rail
- Special gearbox (4 gears) with adjustable band brake
- Full casing
- P.T.O shaft fast rewind
- Hydraulic support legs at the back
- Lockable turntable
- Return stop at the pipe drum
- Mechanical safety shut-down against winding faults
- Fully galvanized water inlet
- Low pressure - and total shut-down
- Electronic speed control with pinion sensor
- 3-wheel sprinkler trolley, with automatic lifting at the end of irrigation
- Large-area sprinkler TWIN 101 ULTRA

Special equipment

- Hydraulic drive for turntable
- Crank support leg at the front
- Pipe guidance device (mechanical)
- Lighting installation
- Solar panel for battery recharging
- Additional sprinkler for close range (electronically controlled)
- GSM control unit
- Water meter DN 65 non-calibrated or calibrated (on request)
- Supply hose DN 90, 8m, 89 female/male
- Discharge hose DN 90, 5m, 89 female
- Large-area sprinkler at choice

Operating principle

HÜDIG has set standards in the development of irrigation machines. For over 100 years now, experience from agricultural irrigation has been used to develop and improve our products.

With the help of a low-maintenance, flanged gear-turbine unit and a drive sprocket bolted to the reel, the PE pipe is pulled in safely even under the highest loads. The feed speed is controlled and monitored by the HÜDIG-Control electronic feed control and a pinion sensor mounted on the gearbox.

The portal axle chassis also guarantees sufficient ground clearance for driving through higher crops.

Equipment



Central control unit

All essential control elements, the HÜDIG-Control electronic feed control and the drive unit are combined in the control center behind a large, lockable cover. The individual elements are clearly arranged and easily accessible.

The drive unit is a free-flow turbine with a directly adapted gearbox. This combination is characterized by good efficiency. Overall, this arrangement impresses with good operating comfort and a high degree of easy maintenance.

The HC 2.009 electronic intake control ensures uniform irrigation intensity. Pre- and post-irrigation according to the conditions can be set intuitively from 1 - max. 250 minutes. Depending on the water supply conditions, draw-in speeds of 5 - 200 m/h are possible. Furthermore, many additional options (e.g. close-range sprinklers etc.) or various draw-in parameters (e.g. start/stop time) can be controlled using HÜDIG-Control.



Portal-axle chassis

The Iromat I RED has a single-axle portal axle chassis as standard. This design ensures a high ground clearance for driving through crops. An agricultural rail hitch is provided as a connecting device.



Automatic sprinkler trolley lifting

At the end of the irrigation cycle, the sprinkler wagon automatically lifting (the energy is taken from the water volume flow required for irrigation). The rear support legs are retracted manually via the oil hydraulics after irrigation is complete. This convenience reduces set-up times to a minimum.



Sprinkler trolley

The 3-wheel sprinkler trolley developed by HÜDIG has exceptional directional stability even on uneven terrain. A robust and wear-free level compensation system prevents the large-area sprinkler from dipping at the end of the irrigation process.

A convenient, central pulling device is available for pulling out the hose in the tractor track with a narrow agriculture rail.

For tall crops, e.g. maize, a maize sprinkler trolley can be used as an option.