

**Application:**

Construction Industry – General Industry – Municipalities

- to jet in wellpoints, wells or piles
- for the water supply at construction sites
- filling and testing of pipe lines
- cleaning construction vehicles and equipment
- fire fighting
- irrigation

**Design:**

HÜDIG high-pressure centrifugal pumps are multistaged, normal priming pumps, suitable for pumping clean or slightly dirty water without solid components. The pumps are driven by a Diesel engine. The pumps should be manually primed.

- mounted on single-axle trailer with pneumatic tyres suitable for construction-site-traffic (6 km/h)
- removable truck draw bar
- battery box and crane hook eye

**Pump:**

$V_{max}$ : 43,5 m<sup>3</sup>/h

$p_{max}$ : 14,5 bar

Connection: suction side - 108 male –

Discharge side - 50 male

4 stages

**Engine:**

Brand: Lombardini

Type: 9 LD

Capacity: 19.2 kW (26.0 PS)

Speed: 3000 min<sup>-1</sup>

Weight: 420 kg

Dimension: length: 1700 mm (without drawbar) x width: 1050 mm x height: 1200 mm

Subject to change without prior notice!

## HÜDIG - your partner to solve water problems.

### HÜDIG®

GmbH & Co. KG

**Absenk- und Beregnungsanlagen**

Heinrich-Hüdig-Straße 2 · 29227 Celle

Telefon (0 51 41) 88 45-0 · Fax (0 51 41) 8 69 18

e-mail: Info@huedig.de